

Green Pin[®] Snatch Block S
Snatch block type 601S with Green Pin[®]
Shackle attached



Highlights

Smooth, uninterrupted pull due to conical roller bearings
Includes Green Pin[®] shackle
Coating assures long-term durability Lightweight
Superior stock availability of 99%

Description

The Green Pin[®] Snatch Block S is a light-weight snatch block type 601S with a Green Pin[®] Shackle attached. The Green Pin[®] Snatch Block S has a smooth, uninterrupted pull due to conical roller bearings. Its coating ensures long-term durability, even under harsh conditions. The Green Pin[®] Snatch Block S is available in a range with a working load limit from 2 up to 30 ton.

Product details

Productcode	P-6951
Material	carbon steel, fitted with conical roller bearings
Safety factor	MBL equals 4 x WLL
Finish	painted
Certi cation	2.1 2.2 MTCb CE
Note	Working Load Limit is on the headfitting



Green Pin® Snatch Block S

Technical specifications in millimeters

Article code	working load limit	diameter wire rope	A diameter outside sheave	B length	C width	D width outside	Nett weight KG
BKOFFSS0302	2	7 - 9	75	293	75	82	3.87
BKOFFSS0404	4	10 - 12	115	363	102	120	6.36
BKOFFSS0604	4	12 - 14	152	417	102	160	8.39
BKOFFSS0608	8	20 - 22	152	477	118	160	14.1
BKOFFSS060816	8	14 - 16	152	477	118	160	14.3
BKOFFSS0612	12	20 - 22	152	555	147	160	20.0
BKOFFSS061216	12	14 - 16	152	555	147	160	20.0
BKOFFSS0615	15	24 - 26	152	585	162	160	24
BKOFFSS0804	4	10 - 12	203	478	102	210	11.0
BKOFFSS0808	8	20 - 22	203	526	118	210	18
BKOFFSS0812	12	20 - 22	203	580	147	210	28
BKOFFSS081216	12	14 - 16	203	580	147	210	27

Technical specifications in millimeters

Article code	working load limit	diameter wire rope	A diameter outside sheave	B length	C width	D width outside	Nett weight KG
BKOFFSS0815	15	24 - 26	203	646	162	210	30.0
BKOFFSS1008	8	20 - 22	254	582	118	260	26
BKOFFSS100816	8	14 - 16	254	582	118	260	26
BKOFFSS1012	12	20 - 22	254	680	147	260	35
BKOFFSS1015	15	24 - 26	254	705	162	260	42
BKOFFSS1208	8	20 - 22	305	612	118	310	31
BKOFFSS1212	12	20 - 22	305	745	147	310	35
BKOFFSS1215	15	24 - 26	305	771	162	310	33
BKOFFSS1408	8	20 - 22	357	662	118	360	31
BKOFFSS1412	12	20 - 22	357	770	147	360	35
BKOFFSS1415	15	24 - 26	357	798	162	360	63
BKOFFSS1422	22	28 - 32	357	906	216	385	94.0
BKOFFSS1608	8	20 - 22	406	712	118	410	35
BKOFFSS1612	12	20 - 22	406	820	147	410	67
BKOFFSS1615	15	24 - 26	406	848	162	410	39
BKOFFSS1622	22	28 - 32	406	963	216	415	139
BKOFFSS1630	30	32 - 38	406	1126	410	415	124

Arti	wor	dian	A di	B le	C w	D w	Net
BKOFFSS1808	8	20 - 22	457	762	118	460	42
BKOFFSS1812	12	20 - 22	457	878	147	460	75
BKOFFSS1815	15	24 - 26	457	898	162	460	44.5
BKOFFSS1822	22	28 - 32	457	1033	216	465	154
BKOFFSS1830	30	28 - 32	457	1083	238	468	218

Technical specifications in millimeters

Article code	working load limit	diameter wire rope	A diameter outside sheave	B length	C width	D width outside	Nett weight KG
BKOFFSS1608	8	20 - 22	406	712	118	410	35
BKOFFSS1612	12	20 - 22	406	820	147	410	67
BKOFFSS1615	15	24 - 26	406	848	162	410	39
BKOFFSS1622	22	28 - 32	406	963	216	415	139
BKOFFSS1630	30	32 - 38	406	1126	410	415	124
BKOFFSS1808	8	20 - 22	457	762	118	460	42
BKOFFSS1812	12	20 - 22	457	878	147	460	75
BKOFFSS1815	15	24 - 26	457	898	162	460	44.5
BKOFFSS1822	22	28 - 32	457	1033	216	465	154
BKOFFSS1830	30	28 - 32	457	1083	238	468	218

Technical specifications in inches

Article code	working load limit	diameter wire rope (inch)	A diameter outside sheave (inch)	B length (inch)	C width (inch)	D width outside (inch)	Nett weight LBS
BKOFFSS0302	2	9/32 - 3/8	3	11 9/16	3	3 1/4	8.53
BKOFFSS0404	4	3/8 - 1/2	4 1/2	14 9/32	4	4 23/32	14.0
BKOFFSS0604	4	1/2 - 9/16	6	16 7/16	4	6 9/32	18.5
BKOFFSS0608	8	3/4 - 7/8	6	18 25/32	4 5/8	6 9/32	31.1
BKOFFSS060816	8	9/16 - 5/8	6	18 25/32	4 5/8	6 9/32	31.4
BKOFFSS0612	12	3/4 - 7/8	6	21 7/8	5 25/32	6 9/32	44.1
BKOFFSS061216	12	9/16 - 5/8	6	21 7/8	5 25/32	6 9/32	44.1
BKOFFSS0615	15	1	6	23 1/32	6 3/8	6 9/32	52.9
BKOFFSS0804	4	3/8 - 1/2	8	18 13/16	4	8 9/32	24.2
BKOFFSS0808	8	3/4 - 7/8	8	20 23/32	4 5/8	8 9/32	39.7
BKOFFSS0812	12	3/4 - 7/8	8	22 13/16	5 25/32	8 9/32	61.7
BKOFFSS081216	12	9/16 - 5/8	8	22 13/16	5 25/32	8 9/32	59.5

Technical specifications in inches

Article code	working load limit	diameter wire rope (inch)	A diameter outside sheave (inch)	B length (inch)	C width (inch)	D width outside (inch)	Nett weight LBS
BKOFFSS0815	15	1	8	25 7/16	6 3/8	8 9/32	66.2
BKOFFSS1008	8	3/4 - 7/8	10	22 29/32	4 5/8	10 1/4	57.3
BKOFFSS100816	8	9/16 - 5/8	10	22 29/32	4 5/8	10 1/4	57.3
BKOFFSS1012	12	3/4 - 7/8	10	26 3/4	5 25/32	10 1/4	77.2
BKOFFSS1015	15	1	10	27 3/4	6 3/8	10 1/4	92.6
BKOFFSS1208	8	3/4 - 7/8	12	24 3/32	4 5/8	12 3/16	68.4
BKOFFSS1212	12	3/4 - 7/8	12	29 5/16	5 25/32	12 3/16	77.2
BKOFFSS1215	15	1	12	30 5/16	6 3/8	12 3/16	72.8
BKOFFSS1408	8	3/4 - 7/8	14	26 1/32	4 5/8	14 5/32	68.4
BKOFFSS1412	12	3/4 - 7/8	14	30 9/32	5 25/32	14 5/32	77.2
BKOFFSS1415	15	1	14	31 3/8	6 3/8	14 5/32	139
BKOFFSS1422	22	1 1/8 - 1 1/4	14	35 21/32	8 1/2	15 5/32	207
BKOFFSS1608	8	3/4 - 7/8	16	27	4 5/8	16 5/32	77.2
BKOFFSS1612	12	3/4 - 7/8	16	32 9/32	5 25/32	16 5/32	148
BKOFFSS1615	15	1	16	33 3/8	6 3/8	16 5/32	86.0
BKOFFSS1622	22	1 1/8 - 1 1/4	16	37 29/32	8 1/2	16 11/32	306
BKOFFSS1630	30	1 1/4 - 1 1/2	16	44 11/32	16 5/8	16 11/32	273

Arti	wor	dian	A dia	B lei	C w	D w	Net
BKOFFSS1808	8	3/4 - 7/8	18	29 31/32	4 5/8	18 1/8	92.6
BKOFFSS1812	12	3/4 - 7/8	18	34 9/16	5 25/32	18 1/8	165
BKOFFSS1815	15	1	18	35 11/32	6 3/8	18 1/8	98.1
BKOFFSS1822	22	1 1/8 - 1 1/4	18	40 21/32	8 1/2	18 5/16	340
BKOFFSS1830	30	1 1/8 - 1 1/4	18	42 5/8	9 3/8	18 7/16	481

Technical specifications in inches

Article code	working load limit	diameter wire rope (inch)	A diameter outside sheave (inch)	B length (inch)	C width (inch)	D width outside (inch)	Nett weight LBS
BKOFFSS1608	8	3/4 - 7/8	16	27	4 5/8	16 5/32	77.2
BKOFFSS1612	12	3/4 - 7/8	16	32 9/32	5 25/32	16 5/32	148
BKOFFSS1615	15	1	16	33 3/8	6 3/8	16 5/32	86.0
BKOFFSS1622	22	1 1/8 - 1 1/4	16	37 29/32	8 1/2	16 11/32	306
BKOFFSS1630	30	1 1/4 - 1 1/2	16	44 11/32	16 5/32	16 11/32	273
BKOFFSS1808	8	3/4 - 7/8	18	29 31/32	4 5/8	18 1/8	92.6
BKOFFSS1812	12	3/4 - 7/8	18	34 9/16	5 25/32	18 1/8	165
BKOFFSS1815	15	1	18	35 11/32	6 3/8	18 1/8	98.1
BKOFFSS1822	22	1 1/8 - 1 1/4	18	40 21/32	8 1/2	18 5/16	340
BKOFFSS1830	30	1 1/8 - 1 1/4	18	42 5/8	9 3/8	18 7/16	481

Technical drawing

